# Primer 20



constructive solutions

#### **Porous surface primer**

#### **Description**

Primer 20 is a high performance single component chemically active, non-toxic liquid for brush application to prime porous surfaces.

#### Advantages

- Easy to Apply
- Strong adhesion

#### **Application**

Open tin lid. Mix thoroughly until a homogeneous dispersion is achieved.

Apply one thin coat using a clean dry brush. Avoid over application of primer causing puddles in the bottom of the joint. Sealants must be applied when the primer has become touch dry, that is after the evaporation of the solvent, but before the primer film has completely reacted. If the primer film has become completely tack free, the surfaces must be reprimed before applying the sealant.

### Cleaning

Clean equipment immediately after use with Fosroc Solvent 102.

## **Estimating**

Supply		
Primer 20:	500 ml can	
Coverage		
Primer 20:	4 - 5 m2 / ltr	

#### **Storage**

#### Shelf life

12 months if stored in the original unopened packs in a cool dry place. Do not store in direct sunlight.

#### **Precautions**

#### **Health and safety**

Primer 20 is flammable liquid. Shall be stored away from heat. and shall not be used near a naked flame. Skin contact shall be avoided. Eye protection and impervious rubber or PVC gloves shall be worn. Splashes must be washed off immediately. Prolonged breathing of vapour shall be avoided.

Hands shall be washed thoroughly before eating or smoking. In the case of eye contact, medical attention shall be sought immediately.

#### **Disposal**

Dispose according to local authority regulations. Do not dispose into sewer or drains.

#### **Additional information**

	<b>Primer</b>	20
_	Clash Da	:1

Flash Point	>50 °C	
Storago Lifo	12 months	
Storage Life	(@ 5 – 25 °C)	
Drying time	20 – 60 min.	
Flash Point-Fosroc	33°C	
Solvent 102	33 C	

For further information on any of the above, please consult your local Fosroc office - as below.



JI.Akasia II Blok A8 No.1 Delta Silicon Industrial Park Lippo Cikarang Bekasi 17550 Indonesia

www.fosroc.com

Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Services, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification of information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it.

**telephone:** +62 21 897 2104-06 fax:

+62 21 897 2107

email:

Indonesia@Fosroc.com